

LANKO



CHARACTERISTICS

- Ready to use.
- Easy to use.
- Fast drying.
- Interior and exterior

PACKAGING

- 1.5 kg container.
- 5 kg container.

STORAGE

1 year from date of manufacture if stored in unopened original packing in cool dry, frost-free conditions.

DESCRIPTION

107 LANKOPUTTY is an acrylic putty, used to fill or patch cracks, nail holes, grooves, seams, air bubbles, rock pockets in various surfaces. Its ready to use formula spreads easily for fast repairs that will not crack, crumble or flake.

USES

Interior and exterior

Permissible substrate

- Concrete.
- Traditional rendering.
- Brick, concrete block, lightweight concrete or light weight block.
- Wood.

SPECIFICATIONS

- Appearance : White paste
- Paste density : 1.75 ± 0.05
- Paste viscosity : 85000 cps
- pH : 8-9

WORK INSTRUCTIONS

Substrate preparation

- The substrate must be clean, sound, dust-free and without any traces of oil, laitance, paint or curing compound.
- Overplus and seams must be struck off.

Product preparation

- Ready to use.
- Stir the product well prior to application.
- No water must be added.

Application

- Apply with putty knife.
- When dry, sand excess flush with the surface.
- For deep cracks or holes, apply two or more layers and allow to dry between each layer.
- Allow to dry thoroughly (1-2 hours depending on temperature) before over painting.

PRECAUTIONS

- Temperature range for use : 5°C - 35°C.
- Clean tools with water before the product dries.
- Do not immerse the product.