

LANKO



CHARACTERISTICS

- **Does not alter surface appearance.**
- **Pearly appearance.**
- **Excellent penetration.**
- **Can be used on damp substrates.**
- **Excellent resistance to weathering agents (UV rays, rain, etc.).**

COVERAGE

Concrete : 0.25 - 0.5 litres/m².
Mortar: 0.5 - 0.8 litres/m²
Cellular concrete : 0.5 - 1 litre/m²

PACKAGING

- 1 litre container
- 5 litre container

STORAGE

1 year from date of manufacture if stored in unopened original packing in dry, frost-free conditions.

DESCRIPTION

231 LANKO WEATHERPROOF is a ready-to-use solvent-base product containing silane/siloxane, It spreads by capillary action and establishes a stronghold within the substrate.

USES

Protection of facades and sloping surfaces :

- Concrete.
- Cellular concrete.
- Hydraulic mortar coatings.
- Fibrous cement.
- Sandstone.
- Brick and roofing tiles.
- Natural stonework.

SPECIFICATIONS

- Appearance : Milky-white liquid.
- Density at 20°C : 0.98

Performance* Typical results are as follows

- Concrete : excellent
- Cellular concrete : excellent
- Roofing tiles and bricks : excellent
- Natural stonework : variable
- Hydraulic mortar coating : excellent
- Fibrous cement : very good

* optimal performance when sufficient quantities are applied

WORK INSTRUCTIONS

Substrate preparation

- The substrate must be clean, sound, dry or slightly damp. After rain, wait at least 24 hours. After high pressure washing, wait at least 3 days.
- Remove efflorescence. Fill cracks.
- Concrete and mortar coatings must be at least 28 days old prior to application.

Application

- Apply by brush, by soaking or by spraying. For spraying, the nozzle must be held very close to the surface in order to ensure product penetration.
- Two coats must be applied. The second coat must be applied once the first coat has lost its sheen.
- Best results are obtained on dry absorbent substrates. However good results are also obtained on slightly damp substrates.
- Clean tools and accidental splashes immediately with white spirit.

PRECAUTIONS

- Gloves and eye protection should be worn by persons with sensitive skin.
- Respect the quantity recommendations.
- Store below 35°C.
- Protect door frames and windows from accidental splashes.
- Clean splashes immediately with white spirit.
- Refer to the safety data sheet.