

LANKO



CHARACTERISTICS

- Suitable for use with all mould types.
- Does not leave traces of oil on concrete surface.
- Protects metal surfaces against corrosion.
- Weather-resistant.
- Can be sprayed.

COVERAGE

- 1 litre/35-50 m² for metal or plastic moulds.
- 1 litre/20-35 m² for wooden or plywood.

PACKAGING

- 20 litre container.
- 200 litre steel drum.

STORAGE

1 year from date of manufacture if stored in unopened original packing in dry, frost-free conditions.

DESCRIPTION

341 MATCHLESS CR is a ready-to-use oil based formwork removal, used for demoulding steam-cured and non steam-cured concrete. It in no way affects subsequent applications of mortar or paint.

USES

Suitable for use with all mould types :

- Metal.
- Wooden or plywood.
- Plastic.

SPECIFICATIONS

- Appearance : Light-brown liquid
- Density : 0.83±0.05
- Flash point : > 80°C
- Freezing point : -10°C

WORK INSTRUCTIONS

Product preparation

- 341 MATCHLESS CR is ready to use, should not be diluted.
- Stir well before use.

Application

341 MATCHLESS CR must be applied to form a uniform film on the mold surface.

- By fine haired brush or roller.
- By swab or sponge.
- By spray.

PRECAUTIONS

- Do not inhale.
- Do not expose to naked flames.
- For spray application, work in well ventilated area.
- Gloves and eye protection should be worn.
- Product must be applied in a regular layer, do not use under or over dosage.