

LANKO

CHARACTERISTICS

- **Ready to use.**
- **Water based.**
- **Stain-free**

COVERAGE

- 8-12 m²/liter (Approx.) depending on formwork.

PACKAGING

- 20 litre container.
- 200 litre steel drum.

STORAGE

1 year from date of manufacture if stored in unopened original packing in dry, frost-free conditions.

DESCRIPTION

342 MATCHLESS CR-W is a ready to use water based formwork removal, produces outstanding release qualities at low cost.

ADVANTAGES

- Easier removal of form-work.
- Saves labour costs in form-removal.
- Saves labour costs in repairing and finishing surfaces of concrete exposed to forms.
- Reduces in cost of further materials otherwise required for repairs to such surfaces exposed to forms by reducing the incidence of blowholes, blemishes and staining.
- Prevent rust formation.
- Saves on form-work by allowing for faster recycling; reducing cost and time for cleaning of forms; and by extending life-time of forms by reducing wear and tear on such forms.
- Highly economical coverage rates may be obtained with no difficulty.
- May be used on wooden, steel and plastic form-work.
- Protects door frames and aluminium fitting from plaster and mortars.
- Produces a clear reproduction of form-work design and texture.
- Yields a clean, stain-free concrete surface that will readily accept paint and other coatings.

USES

Wherever quick and easy removal of form-work is required that does not impair or destroy surface finish such as in :

- Pre-cast factories.
- For the construction of columns and beams.
- Construction joints in concrete floor slabs.

SPECIFICATIONS

- Appearance : Amber Liquid
- Density : 0.90

WORK INSTRUCTIONS

- 342 MATCHLESS CR-W is a liquid with very low viscosity. It may be applied by spraying or by brushing. Delivered in ready to use form.
- Stir with hand-tools or drilling machine before using. The mix remains stable for 6-7 days. May be used on dry or damp formwork.

PRECAUTIONS

- Non-toxic, wash off with water and detergents. If contact with eyes, rinse with clean water without rubbing and contact eye-doctor. Keep product away from heat sparks and open flames.



www.lanko.com.au
www.parexlanko.com

The information provided in this document results from our knowledge of the products and our experience. On-site results may vary, in particular according to the product application methods adopted. Where application methods not representative test before using the products. The above-mentioned information in no way constitutes a warranty relative to the use of the products. Our general terms and conditions of sale shall prevail, in any event, on the information provided in this document. Prior to application, customers and users are requested to check that they have the latest version of this document.

Technical Documentation English-Version Aug 2006

Davco Construction Materials (Thailand) Co., Ltd.

3rd Floor Lumpini II Building 247 Sarasin Road, Lumpini, Pathumwam, Bangkok 10330 Telephone: 66(0)2651 9027-36 Facsimile: 66(0)2651 8003
e-mail : thaicustomerservice@davco.co.th, Overseas Offices : Australia (Sydney - Head Office), Singapore

