

**LANKO**

## CHARACTERISTICS

- **Water based.**
- **Stain-free**
- **Highly Economical.**

### COVERAGE

1 litre concentrate for approximately 260-310 m<sup>2</sup>.

### PACKAGING

- 20 litre container.

### STORAGE

1 year from date of manufacture if stored in unopened original packing in dry, frost-free conditions.

## DESCRIPTION

342 MATCHLESS CR-W30 is a highly concentrated substance which, when diluted with water, produces outstanding release qualities at low cost.

## ADVANTAGES

- Easier removal of form-work.
- Saves labour costs in form-removal.
- Saves labour costs in repairing and finishing surfaces of concrete exposed to forms.
- Reduces in cost of further materials otherwise required for repairs to such surfaces exposed to forms by reducing the incidence of blowholes, blemishes and staining.
- Prevent rust formation.
- Saves on form-work by allowing for faster recycling; reducing cost and time for cleaning of forms; and by extending life-time of forms by reducing wear and tear on such forms.
- Highly economical coverage rates may be obtained with no difficulty.
- May be used on wooden, steel and plastic form-work.
- Protects door frames and aluminium fitting from plaster and mortars.
- Produces a clear reproduction of form-work design and texture.
- Bigger mixes may be made at one time at site as mix of concentrate with water remains stable for 6-7 days. If it separates after longer periods of time, it may be re-mixed again with hand-tools or drilling machine.

- Yields a clean, stain-free concrete surface that will readily accept paint and other coatings.

## USES

Wherever quick and easy removal of form-work is required that does not impair or destroy surface finish such as in :

- Pre-cast factories.
- For the construction of columns and beams.
- Construction joints in concrete floor slabs.

## SPECIFICATIONS

- Appearance : Amber Liquid
- Density : 0.85

## WORK INSTRUCTIONS

- 343 MATCHLESS CR-W30 is a liquid with very low viscosity. It may be applied by spraying or by brushing. Delivered in concentrated form at sites. Must be mixed with water in ratio 1 part concentrate to 25-30 parts water. Stir with hand-tools or drilling machine after mixing. The mix remains stable for 6-7 days. May be used on dry or damp formwork.

## PRECAUTIONS

- Non-toxic, wash off with water and detergents. If contact with eyes, rinse with clean water without rubbing and contact eye-doctor. Keep product away from heat sparks and open flames.



[www.lanko.com.au](http://www.lanko.com.au)  
[www.parexlanko.com](http://www.parexlanko.com)

Technical Documentation English-Version Aug 2006

### Davco Construction Materials (Thailand) Co., Ltd.

3rd Floor Lumpini II Building 247 Sarasin Road, Lumpini, Pathumwam, Bangkok 10330 Telephone: 66(0)2651 9027-36 Facsimile: 66(0)2651 8003  
e-mail : thaicustomerservice@davco.co.th, Overseas Offices : Australia (Sydney - Head Office), Singapore

**LANKO**

PAREXGROUP