

LANKO



CHARACTERISTICS

- Ready to use.
- Protects mortar and concrete from drying out.
- Reduces cracking and shrinkage. Can be sprayed.

COVERAGE

- 1 litre/5-8 m²

PACKAGING

- 20 litre container.
- 200 litre steel drum.

STORAGE

1 year from date of manufacture if stored in unopened original packing in dry, frost-free conditions.

DESCRIPTION

361 LANCURE forms a continuous film on the surface of fresh concrete and mortar. The film delays the evaporation of water content in sunny/windy conditions and promotes correct binder hydration, even at the surface.

USES

- All cases in which climatic conditions (sun, wind) accelerate the evaporation of water used in mixing.
- Structure with a high surface : volume ratio.
- To reduce cracking and shrinkage in the following situations :
 - Traffic surfaces : roads, motorways, bridges, embankments, canals, airport runways.
 - Protection of concrete walkways, terraces and flooring.
 - Protection of reservoirs, tunnels, galleries, vaults.

SPECIFICATIONS

- Appearance : Light-violet liquid
- Density : 1.1
- pH : 11.5

WORK INSTRUCTIONS

Product preparation

- 361 LANCURE is ready to use, should not be diluted.
- Stir well before use.

Application

- 361 LANCURE must be applied pure onto the surface of the concrete or mortar as soon as it begins to turn matt.
- Ensure that surfaces are not running with water prior to application.
- If a coating is to be applied to the surface, 361 LANCURE should be removed by washing with water after drying.
- The product film will disappear in time due to weathering or abrasion.

PRECAUTIONS

- Do not inhale.
- For spray application, work in well ventilated area.
- Gloves and eye protection should be worn.
- Product must be applied in a regular layer, do not use under or over dosage.