

LANKO

CHARACTERISTICS

- Easy to apply with brush or roller.
- Good impregnating characteristic.
- Very good adhesion to all kinds of substrates.
- Fast drying.
- Excellent weather resistance.

COVERAGE

- Approx. 100 cc /m²
(depending on substrate).

PACKAGING

- 1 litre can.

STORAGE

1 year from date of manufacture if stored in unopened original packing in dry, frost-free conditions.

DESCRIPTION

608 PU/PS PRIMER is single component ready-to-use primer for polysulphide sealants.

It is recommended to prime existing or old surface prior to applying 603 POLYURETHANE or 607 PS SEALANT.

USES

For porous substrates :

- Concrete.
- Stone.
- Brickwork.
- Timber.
- Unglazed edges of ceramic tiles.

SPECIFICATIONS

- Appearance : White milky liquid
- Density : 0.97
- Viscosity : < 100 cps/25°C
- Solid content w/w : 38 - 42%

WORK INSTRUCTIONS

Substrate preparation

- The substrate must be clean, sound, dry, dust-free and without any traces of oil, grease, laitance, paint and curing compound.
- Powdery materials and old coverings must be removed.

Product preparation

- Stir the product well before using.
- Apply directly from the can.

Application

- Apply a single continuous coat using a clean brush to ensure complete coverage, avoid over-priming resulting in excess of primer at the base of joint.
- Allow tack free (approx. 20-30 minutes depending on the temperature) before applying 603 POLYURETHANE or 607 PS SEALANT

PRECAUTIONS

- Application of 608 PU/PS PRIMER should not be carried out at below 4°C.